

Ruggedized Hand-Held Computer

BIP-6000



pibion
Empowering Mobility

BIP-6000



Retail



Public Transport



Hospitality



Healthcare



Finance

KEY FEATURES & BENEFITS

Ultimate Form Factor



IP65, 1.8m Drop, MIL-STD 810F

BIP-6000 allows working without any restraints of harsh work environment. It meets IP65 sealing requirements, withstands 12 drops at 1.8 m to steel surface and operates in a temperature range of -30°C to 60°C. In addition, powerful 4,400mAh battery ensures continuous operation for a full day.

Revolutionary Integration



RFID Reader, Barcode Scanner, 3MP Camera

BIP-6000 gives an ability to manage more data faster. Integrated RFID Reader and 1D/2D Barcode Scanner enable versatile data capture in a single device. Moreover, 3.0 megapixel autofocus camera with flash supports snapping sharper images from a short distance and under dim light.


Latest Technologies



806MHz PXA 320, Windows Mobile 6.1

BIP-6000 features the full range of latest technologies. 806MHz processor and Windows Mobile 6.1 operating system deliver maximum computing power with easy operation and system integration capability. It supports large memory capacity with 256MB RAM 512MB ROM and MicroSD slot.

Flexible Communications



HSDPA, WiFi, Bluetooth, A-GPS

BIP-6000 provides accuracy and speed data capability for improving work efficiency and flexibility. HSDPA, WiFi and Bluetooth enable real-time communications between mobile workers and head office. An integrated A-GPS allows tracking user position and streamlining route plan.

Outstanding Ergonomics



3.5" VGA, TouchWindow LCD, Numeric/QWERTY

The large 3.5" VGA display gives visual and tactile enhancement. Moreover, the crack-resistant TouchWindow LCD supports substantial protection for the touch sensitive display. Additionally, Numeric/QWERTY keypad with backlight enables easy and precise typing in any light level.

Ruggedized Hand-Held Computer



Warehousing Field Force Automation Logistics Construction Government/Public Sector

APPLICATIONS

Parcel Delivery	Meter Reading	Public Safety	Patient/Pharm Tracking	Work Order Tracking	Fleet Management	Customer Management	Asset Management	Inventory Management	Facility Management

- 1D Barcode & PDF417**
Laser Class II
- 2D Barcode**
CMOS Imager
- RFID**
RFID Reader
- GPS**
Integrated A-GPS
- Camera**
3.0 megapixel,
Autofocus, Flash
- CPU**
PXA 320, 806MHz
- Memory**
256 RAM / 512 ROM
- Battery**
3.7V, 4,400mAh, Li-ion
- Bluetooth**
Bluetooth Class II V 2.0+EDR



BIP-6000

SPECIFICATIONS

PHYSICAL CHARACTERISTICS	
DIMENSIONS (W x H x D)	80 x 160 x 35.5mm / 3.1 x 6.9 x 1.4 inch
WEIGHT	Including battery: 407g
DISPLAY	3.5" VGA with backlight, TFT TouchWindow LCD, 260K, 480 x 640 3.5" QVGA with backlight, TFT TouchWindow LCD, 260K, 240 x 320
TOUCH PANEL	Analog resistance type
KEYPAD	Numeric / QWERTY
BATTERY	Rechargeable, 3.7V, 4,400mAh, Li-ion
EXPANSION SLOT	Customer-accessible MicroSD slot for removable memory card up to 8G
SIM/SAM SLOT	1SIM / 1SAM
AUDIO	High Volume speakers, Headset jack
CAMERA	3 megapixel autofocus camera with LED flash
GPS	Integrated GPS with Network Independent A-GPS
PERFORMANCE CHARACTERISTICS	
CPU	PXA 320, 806MHz
OS	Windows Mobile 6.1 / Windows CE 6.0
MEMORY	256MB RAM / 512MB ROM
INTERFACE	RS-232C, USB 2.0(full-speed) Host & Client, Ethernet via cradle
USER ENVIRONMENT CHARACTERISTICS	
OPERATING TEMP	-30°C to 60°C / -22°F to 140°F, MIL-STD 810F, Method 501.4, Procedure II, Method 502.4, Procedure I,II&III
STORAGE TEMP	-40°C to 70°C / -40°F to 158°F, MIL-STD 810F, Method 501.4, Procedure I, Method 502.4, Procedure I,II&III
TEMP SHOCK	MIL-STD 810F, Method 503.4, Procedure I (-35°C/65°C)
HUMIDITY	MIL-STD 810F, Method 507.4, 90%RH temp cycle 0°C/70°C
DROP	6ft./1.8m drop to steel surface, 2 drops per 6 sides; meets and exceeds MIL-STD 810F
SAND AND DUST	IP65, MIL-STD 810F, Method 510.4, Procedures I&II, KWF-test certified
WATER	IP65, MIL-STD 810F, Method 516.5, Procedure IV, KWF-test certified
VIBRATION	MIL-STD 810F, Method 514.5, Procedure I&II
ALTITUDE	MIL-STD 810F, Method 500.4, Procedure I,II&III, 15,000 ft at 23°C/73°F
INTEGRATED RADIO	
WWAN RADIO	GSM / HSDPA (850, 900, 1800, 1900, 2100 MHz)
WLAN RADIO	IEEE 802.11b/g
WPAN RADIO	Bluetooth Class II V2.0+EDR, IrDA 1.2
DATA CAPTURE	
BARCODE SCANNER	1D&PDF417 Laser Class II or 1D&2D CMOS Imager
RFID READER	Intergrated RFID, ISO 14443 A/B (MIFARE, Calypso), ISO 15693



ACCESSORIES



Cradle

Battery

Protection Film

Adapter

Adapter Connector

USB Cable

Stylus Pen

Tether

Bluebird

1242, Gaepo-dong, Kangnam-gu, Seoul, Korea (ROK)

T. +82. 70.7730.8000 F. +82. 2.548.0870

www.mypidion.com www.bluebird.co.kr cn.bluebirdsoft.com

BR-BIP-6000-EN-FEB10-V1

Copyright © 2010 Bluebird Soft Inc. All rights reserved.

Bluebird and Pidion are registered trademarks and symbols of Bluebird Soft Inc.

Features and specifications are subject to change without prior notice.